



Stokergaarden.dk

**Tekniske data STG Multi Burn  
mål i mm**

	A	B	C	D	E	F	I	J	K/tilstutning "	L Røgrør Ø	Vægt kg.
<b>STG 17 Kw.</b>	1640	780	1940	1500	1690	820	1310	460	5/4"	150	700
<b>STG 27 Kw.</b>	1640	780	1940	1500	1690	820	1310	460	5/4"	150	700
<b>STG 40 Kw.</b>	1640	780	1940	1500	1690	820	1310	460	5/4"	150	800
<b>STG 60 Kw.</b>	1640	780	1940	1600	1850	820	1415	460	5/4"	180	1000
<b>STG 80 Kw.</b>	1960	950	2150	2180	1950	950	1695	660	2"	180	1150
<b>STG 100 Kw.</b>	1960	950	2150	2180	2130	950	1695	660	2"	200	1200
<b>STG 150 Kw.</b>	2350	1300	2600	2350	2500	1300	2030	805	DN 80	250	1750
<b>STG 200 Kw.</b>	2350	1300	2600	2350	2500	1300	2030	805	DN 80	250	1950
<b>STG 250 Kw.</b>	2350	1300	2600	2350	2500	1300	2030	805	DN 80	250	1950
<b>STG 300 Kw.</b>	2450	1300	2600	2450	2600	1300	2110	805	DN 100	345	2100
<b>STG 350 Kw.</b>	3220	1774	3900	3220	3370	1774	2680	990	DN 125	345	4600
<b>STG 400 Kw.</b>	3220	1774	3900	3220	3370	1774	2680	990	DN 125	345	4600
<b>STG 450 Kw.</b>	3220	1774	3900	3320	3370	1774	2780	990	DN 125	398	4600
<b>STG 500 Kw.</b>	3570	1774	3900	3570	3815	1774	3110	990	DN 125	398	5400
<b>STG 600 Kw.</b>	3570	1774	3900	3570	3815	1774	3110	990	DN 125	398	5400